



Open vSwitch

## OVN4NFV – SFC

By:

Kuralamudhan Ramakrishnan([kuralamudhan.ramakrishnan@intel.com](mailto:kuralamudhan.ramakrishnan@intel.com)) | October 8<sup>th</sup>, 2020


Acknowledgement:  
Srinivasa Addepalli, Ritu Sood

# Agenda


- Why network functions in Edge & K8s clusters?
- Edge-computing scenario to describe the K8s networking requirements
- Networking requirements
- OVN4NFV –SFC
- SDEWAN Use case

# Application Transformation

(AR/VR apps, Gaming, Analytics and Even traditional applications due to sovereignty and context)




- Proximity
- Data sovereignty
- Economics
- Context




Centralized computing to Geo distributed computing

An App consisting of four Micro-services  
ms1 talks to ms2, ms2 to ms3 and ms3 to ms4  
ms1" is user facing service  
"ms1", "ms2" are expected to be there together  
"ms2" is stateful and hence need to talk to each other


# Current/In-progress Edge computing deployments : Multi-Cloud and Multi-Edge




# Challenge : Under utilization of resources



# Challenge: Multiple Site level orchestrators leading to wasting of resources




# Ask : All in One



# How does NFV based deployment with Cloud-native applications look like (Taking SDWAN with security NFs as an example)


[View in Slide show](#)



**Mx**

Desktop/laptop/servers

# Networking Requirements



Feature Reqmts	Dynamic virtual Networks	Provider networks	Multiple interfaces	Network function chaining	Network function load balancing
Considerations	No changes to NFs	No changes to Apps	Configuration via operators	Finite network SRIOV Overlay networking	Smart NIC friendly & AF_XDP for packet processing NFs

# Why did we choose OVN in for Edge Networking?

One of the best programmable controller

Hides OVS complexity

Broader eco-system


L2 CNI – Support for unicast, multicast, broadcast applications

One site level IPAM – No IP address restriction with number of nodes

Possible to implement critical features with table based pipeline  
(Firewall, Routing, Switching, Load balancing)

SmartNIC friendly

# OVN for K8S and NFV Architecture blocks




## NFN Operator:

- Exposes virtual, provider, chaining CRDs to external world.
- Programs OVN to create L2 switches.
- Watches for PODs being coming up
  - Assigns IP addresses for every network of the deployment.
  - Looks for replicas and auto create routes for chaining to work.
  - Create LBs for distributing the load across CNF replicas.

## NFN agent:

- Performs CNI operations.
- Configures VLAN and Routes in Linux kernel (in case of routes, it could do it in both root and network namespaces)
- Communicates with OVSDB to inform of provider interfaces. (creates ovs bridge and creates external-ids:ovn-bridge-mappings)

# Network traffic between pods



# Virtual Network CR

```
apiVersion: k8splugin.opnfv.org/v1alpha1
kind: Network
metadata:
  name: ovn-priv-net
spec:
  cniType: Ovn4nfv
  ipv4subnets:
    - subnet: 172.16.33.0/24
      name: subnet1
      gateway: 172.16.33.1/24
      excludeIps: 172.16.33.2 172.16.33.5..172.16.33.10
```

Creates OVN Switch with this configuration

# Dynamic Multiple Network Interfaces

## Pod Annotation

```
k8splugin.opnfv.org/nfn-network: '{ "type": "ovn4nfv", "interface": [  
    { "name": "ovn-priv-net", "interfaceRequest": "eth1" },  
    { "name": "ovn-prot-net", "interfaceRequest": "eth2" }  
}]'
```

- Assumes primary/first interface provided by another CNI
- Supports Static IP addresses

# Provider Network CR

```
apiVersion: k8splugin.opnfv.org/v1alpha1
kind: OvnProviderNetwork
metadata:
  name: ovn-provider-net
spec:
  cniType: Ovn4nfv
  ipv4subnets:
  - subnet: 172.16.33.0/24
    name: subnet1
    gateway: 172.16.33.1/24
    excludeIps: 172.16.33.2 172.16.33.5..172.16.33.10
  providerNetworkType: vlan
  vlan:
    vlanId: 100
    providerInterfaceName: eth0
    Node: node1,node2
    logicalInterfaceName: eth0.100
```

Create OVN Switch and configures nodes

# Provider Network Functionality

- CR creates OVN Switch
- Per Node (can be list of nodes, “all” nodes or “any” node)
  - Creates VLAN interfaces
  - Creates OVS Bridge and attaches VLAN interface
  - Configure ovs external-ids:ovn-bridge-mappings
- Pod annotation for attaching Provider network to a Pod

```
k8splugin.opnfv.org/nfn-network: '{ "type": "ovn4nfv", "interface": [  
    { "name": "ovn-provider-net", "interfaceRequest": "net0" }  
}]'
```


# Network Chaining CR

```
apiVersion: k8splugin.opnfv.org/v1alpha1
kind: NetworkChaining
metadata:
  name: chain1
  namespace: vFW
spec:
  type: Routing
  routingSpec:
    leftNetwork:
      - networkName: ovn-provider1
        gatewayIP: 10.1.5.1
        subnet: 10.1.5.0/24
    rightNetwork:
      - networkName: ovn-provider1
        gatewayIP: 10.1.10.1
        subnet: default
networkChain: app=slb, ovn-net1, app=ngfw, ovn-net2, app=sdwancnf
```


Inserts routes in Container Namespaces

# Software Defined Edge WAN (SDEWAN)




[View in Slide show](#)



WAN



WAN



## SD-EWAN

- Open WRT based SE-DWAN CNFS
- Cloud Native based SD-EWAN controller and IPSec controller
- Zero touch automation
- Solution to all Edge Challenges identified
- Centralization controller for configuration
- Traffic Hub for sanitization

## Advantages


- No changes to application Micro services and configuring Edges
- Supporting both green field and brownfield requirements
- Work with third party SD-WAN VNFs (future roadmap)

Refer

Repo:  
<https://gerrit.akraino.org/r/admin/repos/icn/sdwan>

# Software Defined Edge WAN (SDEWAN)

[View in Slide show](#)



## SD-EWAN

- Open WRT based SE-DWAN CNFS
- Cloud Native based SD-EWAN controller and IPSec controller
- Zero touch automation
- Solution to all Edge Challenges identified
- Centralization controller for configuration
- Traffic Hub for sanitization

## Advantages



- No changes to application Micro services and configuring Edges
- Supporting both green field and brownfield requirements
- Work with third party SD-WAN VNFs (future roadmap)

Refer

Repo:  
<https://gerrit.akraino.org/r/admin/repos/icn/sdwan>

# Software Defined Edge WAN (SDEWAN)

[View in Slide show](#)



## SD-EWAN

- Open WRT based SE-DWAN CNFS
- Cloud Native based SD-EWAN controller and IPSec controller
- Zero touch automation
- Solution to all Edge Challenges identified
- Centralization controller for configuration
- Traffic Hub for sanitization

## Advantages




- No changes to application Micro services and configuring Edges
- Supporting both green field and brownfield requirements
- Work with third party SD-WAN VNFs (future roadmap)

Refer

Repo:  
<https://gerrit.akraino.org/r/admin/repos/icn/sdwan>

# Software Defined Edge WAN (SDEWAN)

[View in Slide show](#)



## SD-EWAN

- Open WRT based SE-DWAN CNFS
- Cloud Native based SD-EWAN controller and IPSec controller
- Zero touch automation
- Solution to all Edge Challenges identified
- Centralization controller for configuration
- Traffic Hub for sanitization


## Advantages

- No changes to application Micro services and configuring Edges
- Supporting both green field and brownfield requirements
- Work with third party SD-WAN VNFs (future roadmap)


Refer

Repo:  
<https://gerrit.akraino.org/r/admin/repos/icn/sdwan>


# Test scenario – to comprehend multiple deployment variations



# Traffic from external entities with sfc



# Traffic from pod within the cluster with sfc




Default route: 172.30.10.3


External existing entities

VNF/CNFs

# Traffic from external entities – Firewall icmp reject



# Traffic from pod within the cluster – Firewall icmp reject



# OVN4NFV Status

## Current

- Dynamic Network Creation
- VLAN Provider Network Support – Controller and Agent
- Direct Provider Network Support – Controller and Agent
- SFC feature – Controller and Agent
- Kubespray default primary network plugin
- Tested with sdewan CNFs and SDEWAN Controller
- Tested with vDPA and OVS offloading as a PoC

Link to Repo:

<https://github.com/opnfv/ovn4nfv-k8s-plugin>

<https://github.com/kubernetes-sigs/kubespray/blob/master/docs/ovn4nfv.md>

# Upcoming features in OVN4NFV

## Work In Progress

- Kubespray Centos CI/CD, SFC advance testing
- Using OVN Load balancer for Kubernetes service(without kube-proxy)
- SRIOV NIC as primary network interfaces
- SFC support with OVN load balancer support for NF Elasticity
- Network policy with OVS
- Proxy less service mesh with OVN & Ipsec in network namespace
- IPv6 support
- Traffic interception method with 5G UPF



Open vSwitch


# OVN4NFV – SFC

By:


Kuralamudhan Ramakrishnan([kuralamudhan.ramakrishnan@intel.com](mailto:kuralamudhan.ramakrishnan@intel.com)) | August 11<sup>th</sup>, 2020

Acknowledgement:  
Srinivasa Addepalli, Ritu Sood

# Test scenario – to comprehend multiple deployment variations



# NFN Operator and Agent Communication





Open vSwitch

# OVN4NFV – SFC

By:

Kuralamudhan Ramakrishnan([kuralamudhan.ramakrishnan@intel.com](mailto:kuralamudhan.ramakrishnan@intel.com)) | August 11<sup>th</sup>, 2020

Acknowledgement:  
Srinivasa Addepalli, Ritu Sood